



**Made in India**



**RMG Polyvinyl India Limited**, an ISO 9001:2015 systems approved company and is one of the largest manufacturer and exporter of PVC Floor Coverings in India with annual production in excess of 40,000MT (27 Million Sq meters) of residential & heavy duty floorings. Winner of Top Export Award for PVC floor Coverings since several years, the products are exported to Asian countries, Europe, Gulf, Africa and the Americas.

RMG's state-of-the-art plant is located at Sikandarabad (UP) in the Delhi NCR region, the capital of India. The factory boasts of modern calendaring, LVT & cushion vinyl lines to deliver the widest range of flooring products which meet international requirements for abrasion, low smoke & fire retardant properties.

The factory also produces PVC leather, PVC Films & PVC Geomembranes.

RMG's flooring is marketed in India and overseas under the flagship brand WONDERFLOOR. The Wonderfloor product range includes floorings for home interiors, offices, education, healthcare, factories, buses & rail coaches, aerobridges, supermarkets, porta cabins, prefabricated shelters and almost all interior applications.





Beige (4501)



Almond Brown (4502)



Black (4508)



Citrus Yellow (4503)



Light Grey (4509)



Tango Orange (4504)



Ash Grey (4510)



Terracotta (4505)



Lily White (4511)



Signal Red (4506)



Carolina Blue (4512)



Sea Green (4507)



Ocean Blue (4513)



Marine Blue (4514)



Super Cream (4515)



Thickness: 1.00/1.50mm/2.00mm/3.00mm  
 Roll Width: 1.50 mtr / 2 mtr  
 Roll Length: 15 / 20 linear mtr

## DUROFLOOR | Heavy-Duty Floorings

These are economically priced, heavy duty floorings having a simple two colour Directional Marble pattern. These are most suitable for Porta Cabins or areas where low cost products are required but performance of a heavy duty flooring is required. These floorings are having a special surface treatment that ensures quick cleaning & low maintenance costs. These floorings are available in rolls and tiles and thickness available from 1.0 mm to 3 mm. The Rolls are available in width of upto 2 Mtrs. & tiles are produced in various sizes.

### Salient Features

- Durofloor is 'M' rated flooring with slip resistance of R9
- Available in a wide range of shade
- Ideal for moderate footfalls
- A cost effective economic flooring solution
- Sound absorption quality
- **Application areas:** Porta Cabins, Pre-fabricated structure, Low budget projects, Warehouse, Labour camps, Shop floors, etc

**Installed at:**

- Daikin AC factory • IIT-Mumbai • PGI, Chandigarh • Fisher Scientific • Sports Authority of India, Lucknow
- Amausi International Hospital • Hindustan Aeronautical Ltd • Prime Surgicals • Bharat Biotech Labs, Hyderabad
- Torrent Pharmaceutical Ahmedabad • Bank Note Press • Zydus Healthcare, Hyderabad • Nuclear Power Corp
- NTPC • Canara Bank • Allahabad Bank • Videocon International



## PERFORMANCE CHARACTERISTICS

CHARACTERISTICS	TEST METHOD	DUROFLOOR
THICKNESS (mm)	EN 428 / ISO 24346	1.00/1.50/2.00/3.00
ROLL WIDTH (mtr)	EN 426 / ISO 24341	1.50 / 2.00
ROLL LENGTH (mtr)	EN 426 / ISO 24341	15 / 20
TILE SIZE (mm)	EN 427	300x300/305x305/610x610*
TOTAL WEIGHT (kgs/sq mtr)	EN 430 / ISO 23997	1.85/2.80/3.75/5.60
SURFACE PROTECTION	PUR	PUR PROTECTION-OPTIONAL
SLIP RESISTANCE	DIN 51130 / ASTM D2047	R9 / PASS
HYGIENE / CLEAN ROOM TEST	ISO 14644-1	Inhibits Growth of Microbes, Class A
RESIDUAL INDENTATION (mm)	EN 433 / ISO 23343-1	≤ 0.10 mm
FLEXIBILITY (mm)	EN 435 / ISO 24344	40 mm MANDREL. PASS
DIMENSIONAL STABILITY (%)	EN 434 / ISO 23999	≤ 0.40%
BEARING CASTOR CHAIR	EN 425 / ISO 4918	SUITABLE / CONTINUOUS
FIRE PROPAGATION	BS 476 PART 6	(I)=10.8 (II)=1.7 } CLASS "0"
SURFACE SPREAD OF FLAME	BS 476 PART 7	CLASS 1
HORIZONTAL & VERTICAL BURNING TEST	IS 15061 - 2002	PASS (ARAI)
REACTION TO FIRE (kw/m2)	EN ISO 9239-1	> 8 / PASS Bfl-S1
PERFORMANCE CLASSIFICATION	EN 685 / ISO 10874	32, 33
ABRASION RESISTANCE	EN: 660-2	WEAR GROUP M
SOUND ABSORPTION	ISO 140-8/EN ISO 717-2	Δ LW = 5db
THERMAL RESISTANCE (m2k/w)	EN 12664 / ISO 8302	<0.00568 - PASS
STAIN RESISTANCE	EN 423 / ISO 26987	1, VERY GOOD RESISTANCE
COLOUR FASTNESS	ISO 105-B02	> BLUE WOOL STANDARD 5
MARITIME USAGES		SUITABLE



### MAINTENANCE

**Do's:** • After laying of flooring, the surface should be cleaned daily with damp mop and weekly or fortnightly with soap solution • Prevent point load indentation by covering your furniture legs with rubber stopper caps • To remove stubborn stains, rub the affected area immediately with a soft coir brush or fine steel wool soaked in a warm soap solution • Scuff marks on the floor can be removed with little application of diesel • Use door coir or suitable mats to minimize accumulation of dust on Wonderfloor vinyl flooring • Use water to remove any chemical spill on flooring.

**Don'ts:** • Do not use any strong detergent, harsh cleaning agent or dry steel wool • Throwing of lighted cigarette butts or match sticks on the floor should be avoided as it could lead to burn marks on the floor • Do not drag any heavy object or furniture on the flooring to avoid scratches on the floor.

**For institutional/bulk enquiries, please e-mail : [mkt@rmgpoly.com](mailto:mkt@rmgpoly.com)**

**or call : +91 9711200510**

**For export enquiries, please e-mail : [info@rmgpoly.com](mailto:info@rmgpoly.com)**

**or call : +91 9873138885 / +91 9953208740**

#### RMG POLYVINYL INDIA LIMITED

Registered Office : UGSR 4, Ansals Plaza, Sector 1, Vaishali Ghaziabad 201 010, (U.P) INDIA. Tel.: +91

120-4284802/803/804/805/806.

Fax: +91 11 66173679. E-mail: [info@rmgpoly.com](mailto:info@rmgpoly.com)

Regional Offices :

- Ahmedabad • Bangalore • Bhubaneswar • Chennai • Chandigarh • Guwahati • Hyderabad • Indore • Kolkata • Kochi
- Lucknow • Mumbai • Pune • Patna

WONDERFLOOR is the registered Trade Mark of RMG Polyvinyl India Limited [www.wonderfloor.com](http://www.wonderfloor.com)



